



SQL

NULL vrednost

SQL: NULLs

```
Select A1, A2, ..., An
From R1, R2, ..., Rm
where vrednost
```

Primer: Prijava studenata baza podataka

Fakultet (Fime, Grad, BrojMesta)
Student (Sid, Sime, Prosek, Vskole)
Prijava (Sid, Fime, Smer, Odluka)

← NULL vrednost:
nedefinisana
ili nepoznata

Student

Sid	Sime	Prosek	Vskole
1	Marko	3.8	580
2	Darko	4.3	400
3	Jelena		620
4	Darko	3.6	300

Prijava

Sid	Fime	Smer	Odluka
1	VTS	SRT	Primljen
1	ETF	RTI	Odbijen
2	ELFAK	Grafika	Primljen
2	FON	SRT	

Prikazati ukupan broj studenata kojima je upisan prosek

```
select count(*)  
From Student  
where Prosek is not null
```

Prikazati ukupan broj studenata u tabeli

```
select count(*)  
From Student
```

Student

Sid	Sime	Prosek	Vskole
1	Marko	3.8	580
2	Darko	4.3	400
3	Jelena		620
4	Darko	3.6	300

Prikazati broj studenata kojima je upisan prosek

```
select count(Prosek)  
From Student
```